Throstle Nest Mill, Leeds Road, Nelson, Lancashire, England B89 7QZ. Phone: 01282 696214.

<u>www.daledoc.co.uk</u> salesoffice@dale-techniche.co.uk

## **TECHNICAL SPECIFICATION**

## SINGLE LAYER, FR COVERALL - ARC1001/15HZ

Garment conforms to:	Flame retardant, anti-static, single layer coverall made from durable 220gsm fabric giving protection against the thermal effects of an electric arc.  EN IEC61482-1-1 (open arc) ATPV = 11cal/cm².  EN IEC61482-1-1 (2.0) ELIM 9.9cal/cm².  EN 61482-2:2020  EN ISO11612:2015 (A1, B1, C1) Protection against heat and flame.  EN1149-5:2018 Discharges of static electricity.
Garment description:	The garment features High collar, label buggy, comfort pleated back, elasticated waist, concealed 2 way main zip with placket and Velcro fastening, vented self-fabric cuffs with Velcro tab fastenings, 2 double layered internal chest pockets, 2 hip pockets with double layered pocket bags, 2 cargo pockets with flaps, adjustable concealed zip closure to leg bottom with Velcro tab, external knee pad pockets with Velcro fastening to bottom.
	Reflective tape as required.
Sizes:	Sizes S to 2XL. Leg lengths short (74cm), regular (79cm) and long (84cm), Larger sizes & MTM upon request
Labels:	CE to EN 61482-2:2020, EN ISO11612:2015, EN1149-5:2018.
Wash Instructions:	Domestic wash at 60°C, No Bleaching, Cool Iron, Can be dry cleaned, Tumble Dry (Low Heat)

Fabric:	56% para aramid, 42% meta aramid, 2% antistatic fibre, woven fabric, 220 gsm, with rip stop grid.
Colour:	Black
Conforms to:	EN ISO11612:2015 A1, B1, C1, EN 1149-3:2004 EN IEC61482-1-1:2019 (open arc) ATPV = 11cal/cm <sup>2</sup> EN IEC61482-1-1 (2.0) ELIM 9.9cal/cm <sup>2</sup>
Sewing thread:	100% meta aramid.

For and on behalf of

**DALE TECHNICHE LIMITED** 

**D** Emmott

**Operations Manager.** 



ertificate number 232