

TECHNICAL SPECIFICATION SHEET

2 LAYER FR COVERALL ARC1032

Garment conforms to:	2 layer flame retardant coverall made from durable 250g & 150g fabric. EN61482-1-1 ELIM 20cal/cm ² , ATPV 20cal/cm ² . EN61482-1-2 APC 2. EN61482-2:2020
Garment standard description:	The garment features include: Action pleated back, elasticated waist, high collar with Velcro fastening, Inner chest pocket, left and right outer chest pockets, pocket to left arm, plain cuffs with Velcro tabs, hip pockets with access pockets, back hip pockets, cargo pocket to left thigh, outer knee pad pockets and plain legs bottoms. FR reflective tape available if required.
Sizes:	XS to 2XL, leg lengths Short, Regular, Tall & Extra Tall. Made to measure upon request.
Labels:	CE to EN61482-2:2020
Outer fabric:	65% FR Viscose, 22% Meta Aramid, 12% PA, 1% Antistatic 250g woven fabric
Colour:	Navy
Fabric conforms to:	EN ISO11612:2015 (A1, B1, C1), EN1149-3:2004 IEC1482-1-1:2019 (open arc) ELIM 8.1cal/cm ² /EBT = 8.7cal/cm ² IEC 61482-1-2:2014 (arc in a box) Class 1 (4KA) EN1149-3:2004
Inner fabric:	64% FR Viscose, 35% Meta Aramid, 12% PA, 1% Antistatic 150g woven fabric.
Colour:	Melange
Fabric conforms to:	IEC61482-1-2:2018 (arc in a box) APC 1 (4KA), IEC61482-1-1:2019 (open arc) ELIM = 6.3cm ² / ATPV = 7cal/cm ² EN ISO11612:2015 (A1, B1, C1) EN1149-3:2004
Sewing thread:	100% meta aramid.

For and on behalf of
DALE TECHNICHE LIMITED

D Emmott

Operations Manager.



Certificate number 2322/00