

www.daledoc.co.uk - www.jaysracewear.co.uk salesoffice@dale-techniche.co.uk

TECHNICAL SPECIFICATION SHEET

SINGLE LAYER, FR WOVEN POLOSHIRT ARC4001

Flame retardant, antistatic polo made from durable 220gsm rip-stop fabric giving protection against the thermal effects of an electric arc.
IEC61482-1-1:2009 Open arc ATPV = 7.7cal/cm² IEC61482-1-1 (2.0) ELIM 6.8cal/cm² IEC61482-1-2:2007 Arc in a box Class 1. IEC61482-2:2020 ISO11612:2015 Protection against heat and flame. EN1149-5:2018 Discharges of static electricity.
The garment features include:
Knitted collar, plain bottom and knitted cuffs. Options –Collar from same fabric as body. 2 or 3 pen pocket on right or left sleeve with or without Velcro fastening to flap. Radio bar. Left and /or right upper chest pockets with or without Velcro or press stud fastened flap. Cuffs with Velcro or press stud adjustable fastening.
FR Reflective tape available if required.
S to 2XL, Made to measure upon request.
CE & UKCA to IEC61482-2:2020, EN1SO11612:2015, EN1149-5:2018.

Fabric:	Nomex® Comfort, woven fabric, 220 gsm, with rip stop grid.
	93% Meta Aramid, 5% Para Aramid & 2% Antistatic.
Colour:	Navy blue – Other colours available upon request.
Conforms to:	EN ISO11612:2015 A1, B1, C1, EN1149-3:2004,
	IEC61482-1-1:2009 (open arc) ATPV = 7.7cal/cm²,
	IEC61482-1-1 (2.0) ELIM 6.8cal/cm ²
	IEC 61482-1-2:2007 (arc in a box) Class 1 (4KA)
Sewing thread:	100% meta aramid.

For and on behalf of **DALE TECHNICHE LIMITED**

D Emmott

Operations Manager.



Certificate number 2322/00